

Condensing Domestic Continuous Flow Gas Water Heater Series



Energy(\$) Saving



Comfort




Safety

Model No.	ECO24e
Installation	External
Ignition	Electronic
L/min. (@ ΔT 25°C)	25.5
No. of bathrooms	2~3
Min. Operating Inlet Water Pressure (kPa)	200
Max. Inlet Water Pressure (kPa)	1000
Mj/Hr	160
Star Rating	6.6 star equivalent*
Efficiency	96.5%
Antifrost	Standard
Solar & High Temperature Compatible	EC24eTA47N, EC24eTA47P
50°C Limited Compatible	EC24eTA45N, EC24eTA45P
Gas Type	NG / LPG / ULPG
Temperature controller	Built-in; up to 4 additional temperature controllers can be installed
Electrical Supply	230VAC-240VAC 50Hz
Unit Height (mm)	753
Unit Width (mm)	458
Unit Depth (mm)	261
Carton Weight (kg)	32
Pipe Connection Size	
NG / LPG	20mm (3/4")
Cold Water	20mm (3/4")
Hot Water	20mm (3/4")

ECO24e

6.6star*



96.5%
Efficiency

Min. 13.5MJ/hr
Max. 160MJ/hr

- ☆ 25.5L hot water flow @ ΔT 25°C
- ☆ For 2~3 bathrooms
- ☆ IP23

* Independently calculated using Australian Standard AS4552. AS4552 limits the rating shown on the energy label to 6.0 Stars. Where the calculated rating of the appliances exceeds 6.0 Stars it is designated as an "equivalent" rating.